

Process Solutions



Husky™ 205

- 1/4 in (6.3 mm) connection
- Max flow: 5 gpm (19 lpm)
- Polypropylene, acetal, PVDF



Husky 307

- 3/8 in (9.4 mm) connection
- Max flow: 7 gpm (26 lpm)
- Polypropylene, acetal



Husky 515

- 1/2 in (12.7 mm) connection
- Max flow: 15 gpm (57 lpm)
- Polypropylene, acetal, PVDF



Husky 716

- 3/4 in (19.1 mm) connection
- Max flow: 16 gpm (61 lpm)
- Aluminum, stainless steel



Husky 1050

- 1 in (25.4 mm) connection
- Max flow: 50 gpm (189 lpm)
- Aluminum, polypropylene, conductive polypropylene, PVDF, stainless steel, hastelloy



Husky 1590

- 1-1/2 in (38.1 mm) connection
- Max flow: 90 gpm (340 lpm)
- Polypropylene, acetal, PVDF, aluminum, stainless steel



Husky 2150

- 2 in (50.8 mm) connection
- Max flow: 150 gpm (568 lpm)
- Polypropylene, PVDF, aluminum, stainless steel, iron



Husky 3275

- 3 in (76.2 mm) connection
- Max flow: 275 gpm (1041 lpm)
- Aluminum



1:1 Fast-Flo®

- Max flow: 5 gpm (19 lpm)
- UL options available



Priming Piston Ink Pump

- Enclosed, dual seal wet cup for longer seal life
- Runaway control with optional DataTrak™



Hydraulic Ink Pump

- Up to 3 times more efficient than pneumatic pumps
- Typical applications:
 - Letterpress inks
 - Lithographic inks



Hydra-Clean®

- High pressure cleaning and sanitizing
- Air-operated for hazardous or confined areas
- 12:1, 23:1, 30:1 or 45:1 ratio options
- Available in wall or cart mount packages

877.84GRACO (1-877-844-7226) or visit us at www.graco.com/process

Air-Operated Double Diaphragm Pumps

- Sizes range from 1.5 to 2.5 in (38 to 64 mm)
- Tri-clamp connections
- Fluid pressure up to 120 psi (8.4 bar, 0.84 MPa)
- Durable, lube-free non-sticking air valve



High Sanitation Diaphragm Pumps

- Flow rates from 90 to 150 gpm (340 to 567 lpm)
- Durable, lube-free non-sticking air valve
- Stainless steel fluid ends can be disassembled in 5 minutes or less
- Interchangeable flapper and ball checks



Piston Pumps

- Fluid transfer and supply of low to medium viscosity fluids
- Flow rates ranging from 4 to 14 gpm (15.1 to 53 lpm)
- Fluid pressure up to 1200 psi (83 bar, 8.3 MPa)
- Double-ball and priming piston designs



3A High Sanitation Diaphragm Pumps

- 3A and EHEDG certifications available
- Flow rates from 90 to 150 gpm (340 to 567 lpm)
- Fluid pressure up to 120 psi (8.4 bar, 0.84 MPa)
- Quick knockdown design for easy cleaning and draining



Bin Evacuation Systems™ (BES)

- Available with two sanitary diaphragm pumps or up to four sanitary piston pumps
- Inflatable wiper seals for increased efficiency and faster change-out of bins
- Evacuate materials from 300 gallon (1,135 l) containers without adding water
- Available with pneumatic or electronic controls



Drum Unloaders

- Unload material from straight-sided or tapered drums
- Inflatable wiper seals for increased efficiency and faster change-out of drums
- Liner guard to prevent bags from entering pump
- Sanitary flange clamps for quick disassembly

